

# PRJ052 External Pressure Pump

This economical pressure pump is best suited for clean water transfer, a small house (1 bathroom) or cabin supply, garden irrigation, suction lift applications, pressure boosting or laundry and garden taps.



- Reliable, efficient power-saving performance.
- Run-dry protection and thermal overload protection to protect the pump.
- 2 year in-field Reefe warranty\*.
- Automatic pressure controller giving consistent pressure supply.
- Special function on the pressure controller that automatically checks for water every 24 hours after a run-dry event.

## Specifications

Width: 190 mm    Length: 370 mm    Height: 380 mm

- Stainless steel casing, shaft and housing.
- Carbon ceramic mechanical seal for reliability.
- IP44 motor with B class insulation (install in a cover).
- Valves assembled, supplied loose for fitting by plumber on site.
- Inline filter should be fitted between pump and tank. Warranty may be void if not installed correctly.
- Quick-plug pressure controller connection.
- Brass barrel union.
- Noryl impeller, jet and venturi for safety and reliability.
- All external pumps supplied with pump cover.

Power		Rated		Maximum		Suction Lift	Water Outlet	Cable Length	Inlet	Outlet
Amps	Watts	Flow (ltr/min)	Head (m)	Flow (ltr/min)	Head (m)		No. of Taps			
2.5	370	25	20	55	33	8 m	2 - 4	3 m	25 FBSP	25 MBSP

\* 2 year warranty is provided by Reefe, not NextGenRoto.